




Standard Configuration & Options Specifications Version 1.2, ENG_INT, March 2022







GENERAL SPECIFICATIONS

•	L.O.A.	11,98m ₁	39'4"
•	Hull length	11,0m	36'1"
•	L.W.L.	10,25m	33' 8'
•	Beam	3,80m	12'6"
•	Ligh displacement (MLC*)	4800kg	10580lbs
•	Ballast (full cast iron)	1550kg	3420lbs
•	Draft	2,25m	7'5"
•	Sail area (upwind)	80m²	861 ft²
•	Engine power (sail drive)	21KW	29HP
•	Fuel capacity	70L	18,5gal
•	Freshwater capacity	200L	53gal
•	EC Certification	I	-

ARCHITECTS/DESIGNERS

- . Naval Architectu: Manuard YD
- . Design: Lorenzo Argento
- Structural Engineering: Pure Design & Engineering .
- Interior design: Gigodesign .
- Concept and R&D: BENETEAU & Seascape

RIG & SAILS DIMENSIONS _____

	Mast length	15,5m	50'10"
	Air draft (excluding antennae)	17,80m	58'5"
•	Mainsail	42m²	452ft ²
	Jib	38m²	409ft ²
	Masthead gennaker	141m²	1518ft ²
	Fractional furling gennaker	58m²	624ft ²

seanapps

STANDARD EQUIPMENT

CONSTRUCTION

• Entire boat structure built in vacuum infused fibreglass with polyester resin

- Fully cored hull with Corecell core and hand-laid vinylester skin coat
- Fully cored deck with a moulded non-slip surface
- Moulded and vacuum infused bulkheads with Mycell (PVC) core
- Fully cored vacuum infused interior modules, designed to serve as
- boat's structure and furniture
- White single tone gelcoat
- Aluminium mast support
- . Cast iron keel with low drag fin and T-bulb; draft 2,25 m / 7' 5", weight 1550 kg / 3420 lbs

Twin vacuum infused composited rudder blades with stainless steel • stock



FIRST 36

RIG & RUNNING RIGGING _

• Deck-stepped tapered Z Spars 9/10 aluminium mast with two sets of swept-back spreaders

- Linked standing rigging with bottle screw adjusters, 1x19 wire rope
- Backstay with purchase, control lines lead to both steering wheels
- Z Spars aluminium boom
- Barton rodkicker/boomkicker
- Robline high-performance halyards (Dyneema cores with polyester covers): mainsail, jib, masthead gennaker, masthead Code0 2:1
- Two 46 Harken Self-Tailing Performa Winch
- Four 40 Harken Self-Tailing Performa Winch
 Four 40 Harken Self-Tailing Performa Winch
- Spinlock XTS halvard clutches on the coachroof

Ronstan blocks and deck equipment for mainsail, jib and gennaker controls

• Robline high-performance running rigging (Dyneema cores with polyester covers): jib & mainsail & gennaker sheets, two mainsail reefs, two tacklines, other control lines

• Ronstan aluminium mainsail traveller system with dedicated mainsail sheet winches at both steering wheels

• Adjustable jib in- and down-haulers for precise 3D trim of the jib

• Wichard folding padeye aft of anchor locker for the staysail deck attachment

DECK EQUIPMENT _

• Stainless steel stantions (60 cm / 2" high) with double lifelines

- Aluminium mooring cleats on the bow, stern and beam
- Jefa steering system with two composite steering wheels in black
 Grabrails on the front of each steering console, with Silva 85E
- compass

• Moulded GRP toerails front and aft of steering wheels for helmsman and crew

• Four Outils Océan rope bags, two at the jib trimmer position & two at the cabin entrance

- Two Outils Océan winch handle bags with two Harken winch handles
 Anchor locker with a hatch
- Stowage compartments for two gas bottles under the port helmsman bench

• Storage compartment under the starboard helmsman bench with breatheable storage bag

• Spacious storage compartment with hatch below the aft cockpit floor between the steering wheels; also for life-raft stowage

• Light-weight foldable bathing platform, build in HoneyComb technology, with lifting system

• Foldable and telescopic bathing ladder on the side of the bathing platform, with a storage bag

INTERIOR _

• Single interior layout: three cabins, one head

SALOON

• Light-weight vacuum infused GRP interior (saloon benches, galley,

ice-box, navigation table) with low-maintenance gelcoat finish

• Central table island (coffee table), with modular & foldable table flaps (plywood, Alpi teak wood veneer)

• Laminated Alpi teak wood veneer fiddles (railing edge) around galley, icebox, navigation table and central table island

· Florrboards made of plywood with durable imitation teak

• Extremely light deck liners (moulded GRP, mat spray painted finish) and side liners (covered in textile)

• Laminated tempered glass windows on both sides of the hull and the sides of the coachroof

- Lewmar Flush Hatch 3G (60 cm x 60 cm / 24 inch x 24 inch) above saloon table and two Lewmar Flush Hatch 3G (21 cm x 40 cm / 8 inch x 16 inch) above galley and navigation table

• Wooden companionway stairs, closing the access to the engine compartment

• Horizontal sliding plexi panel, with dial combination cam lock

- Plexi companionway washboard in three parts foldable bottom piece and two removable panels
- Comfortable cushions for saloon benches in light grey
- Indirect LED lights on the ceiling
- Headroom: 1,88 1,80 m / 6' 2" 5' 11"

GALLEY

- L-galley on the port side of the saloon
- Eno gimbaled gas marine stove (2 burners) with oven
- Gas installation with safety tap
- Galley working surface covered with Kerrock
- Cupboards above the galley (plywood, Alpi teak wood veneer)
- Bottles storage next to the stove
- Single rectangular stainless-steel sink with a freshwater tap & plumbing
- Trash bin next to the sink, with the top opening

• Locker with drawers below the sink (three drawers, white plywood covers)

• Central top-loading icebox (70 L / 18,5 US Gal)

NAVIGATION TABLE

- Navigation table on the starboard side of the saloon
- Chart compartment with top opening
- Cupboard with electric panel and storage above the table (plywood, Alpi teak wood veneer)
- Adjustable spotlight in white or red
- 2x USB-A & 230V socket

 \cdot $\;$ Installation of all main electric systems behind and under the navigation table

FRONT CABIN

- Comfortable V berth (2,02 m x 2,00 m – 0,80 m / 6' 7" x 6' 7" - 2' 7") with cushion

• Locker with shelves & for hangers (plywood, Alpi teak wood veneer), with top fiddle

Storage compartments under V-berth and locker

• Shelve with fiddle (plywood, Alpi teak wood veneer) along both sides of the cabin with indirect LED lights

Two reading spotlights with integrated USB-A sockets

- Lewmar Low Profile hatch (60 cm x 60 cm / 24 inch x 24 inc) above the berth

- Lewmar Flush Hatch 3G (21 cm x 40 cm / 8 inch x 16 inch) above the entrance

• Headroom at the entrance: 1,87 / 6' 1"

AFT CABINS - PORT & STARBOARD

• Comfortable berth (2,02 m x 1,35 m / 6' 7" x 4' 4") with cushion

- Innovative removable bed slats for the inside berth, enabling easy
- access to the storage space underneath or its easy removal

• Locker with shelves & for hangers (plywood, Alpi teak wood veneer), with top fiddle

• Shelve with fiddle (plywood, Alpi teak wood veneer) along with the cabin with indirect LED lights

- Two reading spotlights with integrated USB-A sockets
- Openings to storage space underneath the outside berth

- Lewmar Flush Hatch 3G (21 cm x 40 cm $\,/$ 8 inch x 16 inch) above the entrance

- · Lewmar Portlight openings towards the cockpit
- Headroom: 1,90 / 6' 3" at the entrance



HEAD

Compact and innovative head compartment

Light-weight vacuum infused GRP with low-maintenance gelcoat finish

- Floor in moulded nonskid surface with shower bilge pump
- Innovative foldable GRP sink above the toilet, tap with hower handle
 Locker with mirror above the sink
- Manual Jabsco toilet with black water tank (50 L / 13,2 US Gal) & plumbing
- Lewmar Flush Hatch 3G (21 cm x 40 cm / 8 inch x 16 inch) above the entrance for ventilation
- Headroom at the entrance: 1,86 / 6' 1"

PROPULSION _

- Yanmar 3YM30 inboard diesel engine, 21 KW / 29 HP
- Sail drive SD25 with Flexofold composite hub folding propeller
- Yanmar B-20 engine control panel with tachometer and fuel gauge
- Fuel capacity: 70 L / 18,5 US Gal
- 12V 50AH AGM engine battery, installed under the ice-box
- Alternator 12V 125A

PLUMBING

- 2x 100 L / 26,4 US Gal rotomoulded freshwater tanks under saloon benches

• 12V pressurised fresh water system

- Plumbing with taps in the galley and head
- Electric & manual bilge pump

ELECTRICITY _

• Simarine customised electric control panel (12V & 230DC) with fluids indicators screen, installed at the navigation table

- 12V electric circuit and 2 x 12V 105 AH AGM service battery, installed under the ice-box

230V/115V installation with 30A battery charger and magnetic circuit breaker

- · 230V or 115V (the USA only) cockpit socket with shore power cord
- 230V or 115V (the USA only) sockets in the galley, next to the

navigation table and in the head

- · Indirect LED lights & spotlights; see each room for details
- Masthead LED navigation, steaming and anchor lights

SEANAPPS

• Seanapps mobile application and GSM/GPS tracker for live control of your boat (trip logs, anchoring) and real-time alerts (entrance sensor & battery status) with a 1-year subscription

OPTIONS SPECIFICATIONS

RIGGING ____

FACNOR FLATDECK FD190 FURLER

- Facnor FlatDeck FD190 furler with furling line
- Furling line jammer and block in the cockpit
- Modified forestay, in lieu of standard

BOWSPRIT WITH ANCHOR SYSTEM

- Vacuum infused GRP bowsprit in black, length 0,98 m / 3' 3"
- Integrated stainless steel anchor crane and roller
- Stainless steel rigid bobstay
- Delta anchor (10 kg / 22 lbs) with 50 m/8 mm / 164 ft/5/16 inch

chain

• Quick Prince DP2 Windlass (12V 700W) with handheld remote control and magnetic circuit breaker

HARKEN HYDRAULICS BACKSTAY

 Harken -6 Integral Backstay Cylinder (25 mm / 1" Bore, 345 mm / 1' 2" Stroke) with integrated handle, placed in the stern central position
 in lieu of standard backstay with rope purchase

BARTON RODKICKER/BOOMKICKER

Barton lightweight fibreglass boomkicker

HALYARDS UPGRADE PACK

- Additional fractional gennaker, jib and staysail halyards
- Robline high-performance ropes with Dyneema cores and polyester covers)
- covers) Additional Ronstan blocks at the mast base
- Jammers are already part of the standard configuration

LAZYBAG

- North Sails lazybag for easy mainsail handling and storage on the boom

- Stiched lazy jacks
- · Lazybag central top panel, fixed with double zip all along with the bag

AXXON CARBON MAST

- · Axxcon carbon mast with aluminium spreaders and boom
- Dyform standing rigging
- Same measurements as standard aluminium mast
- Fits the same sails & deck fittings as standard aluminium mast

SAILS ____

NORTH SAILS TRI-RADIAL LAMINATE MAINSAIL & JIB WITH HANKS

Mainsail

- Durable and robust NPL Tour laminate in light grey
- Tri-radial cut with full battens and three reefs, 39 m2 / 420 sq. ft.
- Plastic Allslip sliders
- Drawstring sail bag





Jib

- Durable and robust NPL Tour laminate in light grey
- Tri-radial cut with four horizontal battens, 36 m2 / 388 sq. ft.
- Telltales window & UV protection on leech and foot (WeatherMax

PSA)

Drawstring sail bag

NORTH SAILS TRI-RADIAL LAMINATE MAINSAIL & FURL-ING JIB (with Facnor FlatDeck FD190 furler option)

Mainsail

- Durable and robust NPL Tour laminate in light grey
- Tri-radial cut with full battens and three reefs, 39 m2 / 420 sq. ft.
- Plastic Allslip sliders
- Drawstring sail bag

Jib

- Durable and robust NPL Tour laminate in light grey
- Tri-radial cut with four vertical battens, 36 m2 / 388 sq. ft.
- RopeLuff Pad, Roller Reefing Sail Structure and telltales window
- UV protection on leech and foot (WeatherMax PSA)
- Drawstring sail bag

NORTH SAILS MASTHEAD GENNAKER in a chosen colour

- Masthead A1.5 gennaker/asymmetric spinnaker
- NorLon NY90 nylon (.75 oz), 141 m² / 1518 sg. ft.
- Drawstring sail bag
- Colour options WHITE, DARK BLUE or BLACK

NORTH SAILS FURLING GENNAKER WITH FURLER in a chosen colour

- Fractional furling gennaker/asymmetric spinnaker
- Anti-Torsion RF Luff Rope and Velcro RF Clew Patch
- Polykote nylon, 58 m2 / 624 sq. ft.
- Facnor FX 2500+ furler set with a spliced continuous furling line
- Furling Box Bag
- Colour options WHITE, DARK BLUE or BLACK

NAVIGATION & ELECTRONICS

AUDIO PACK (FUSION MARINE STEREO)

Fusion MSRA210 FM radio with Bluetooth connectivity, installed at the navigation table

Four Fusion XS40 waterproof speakers (4-inch, 120 W), two in the cockpit and two in the saloon

GARMIN COASTAL PACK

Two GMI 20 large and bright 4" QVGA colour displays with LED backlighting, installed one below each jib & gennaker trim winch

- Airmar DST810 depth, speed and temperature transducer
- gWind race wired wind transducer on 1 m / 3' 3" high pole
- Three GNX 120 high-precision backlit LCDs with bold 51 mm / 2" digits, installed on the bracket under the boom

VHF 215i installed at the navigation table with GHS 11i wireless handset, VHF antenna

- AIS 800 Transceiver Black Box for AIS Class A & B transmission
- GA 38 GPS/GLONASS antenna Dedicated switch on the control panel

GARMIN OFFSHORE PACK

- Entire Garmin Coastal pack components
- Reactor[™] 40 Autopilot computer
- Class B Compact Hydraulic Drive Unit
- Solid-state 9-axis Attitude Heading Reference System (AHRS)
- GHC 20 4" QVGA colour displays with autopilot controls
- Reactor[™] Autopilot Remote Control
- Shadow Drive Technology to maintain control, even when the autopilot is engaged
- Dedicated switch for an autopilot on the control panel

GARMIN CHARTPLOTTER

GPSMAP 923 touchscreen chartplotter with high-resolution IPS display

- Supplied with Worldwide Base map, without detailed charts
- Garmin Sailassist™ sailing features
- Installed on grabrail at the steering wheel with custom build aluminium bracket

GARMIN AIS 800 Transceiver

Garmin AIS 800 Blackbox Transceiver, including VHF antenna splitter

SOLAR PACK

- Sunbeam Tough series walkable 111W solar in black
- Placed on the cabin in front of the mast with connection cable hidden under the panel
 - Regulator and dedicated fuse

ELECTRIC INVERTER 230V

- 800W 12V electric inverter to 230V
- Installed at the navigation table
- Not available for the USA

ELECTRIC INVERTER 115V

- 800W 12V electric inverter to 115V
- Installed at the navigation table
- Available only for the USA

115V SOCKETS (IN LIEU OF 230V, USA ONLY)

- Changes 230V sockets in the galley, at the navigation table and in the head to 115V compliant
- Changes shore power cord and cockpit socket to US compliant
- Available only for the USA



FIRST 36

EXTERIOR _

MOORING PACK

- Mooring lines 12m/16mm / 39'/5/8 inch with spliced ends, 4x
- Outils Océan Custom square foam fenders with fixation ropes, 4x

REMOVABLE COCKPIT TABLE

Cockpit attachment points for removable cockpit table in cruising mode

- Stainless steel central support
- Foldable wooden flaps with folding brackets

MODULAR COCKPIT BENCH EXTENSIONS

- Cockpit bench extensions, one piece on each side, for additional seating and sunbathing surfaces
- Offers additional storage volume, with top-down hatch
- Smart recess on the hatch for rope storage and neat cockpit
- Easily removable, build in light GRP

CUSHIONS FOR COCKPIT BENCHES

- Comfortable cushion for cockpit benches and bench extensions
- Water repellent faux leather in grey
- One for each side of the cockpit
- Fixation

COCKPIT SHOWER

- · Cockpit shower handle and tap on the stern of the cockpit
- Cold freshwater

SPRAYHOOD

- Rigid stainless steel structure
- Sunbrella UV stable fabric on the top
- Strataglass windows towards the bow

COCKPIT BIMINI

• Additional coverage of the cockpit between sprayhood and mainsail shee, not covering helmsman position at steering wheels

• Sunbrella UV stable fabric

SUNSHADE

- Shading panels fixed under the bom
- In the front fixed on the shrouds
- On the stern corners supported with poles
- Sunbrella UV stable fabric

MARINE BEAN BAG

- Rectangular bean bag for additional comfort on and below the deck
- Spliced fixation rope with plastic snap-shackle
- Colours combinations GREY/WHITE and GREY/BLUE

INTERIOR

FRIDGE COMPRESSOR

- Upgrade of the standard ice-box with Danfoss compressor/ evaporator & controller
- Dedicated switch on the electric control panel

SEA & FRESHWATER TAP WITH ELECTRIC PUMP

- Single sea & freshwater water mixing tap in the galley, instead of additional seawater tap
- Additional 12V water-pressure pump & plumbing for seawater

CUTTING BOARD EXTENSION

- Wooden cutting board with hooks
- Connecting galley and ice-box for additional working surface
- Easily removable,

WATER HEATER (25 L / 6.6 GAL)

- QUICK B3 500W 25 L / 6.6 GAL water heater
- 230 V / 115 V electric heater & engine heat exchange
- Plumbing in galley, head and cockpit shower (if ordered)

WEBASTO FORCED AIR DIESEL HEATER (AIR TOP EVO 40D)

- Webasto AIR TOP EVO 40D diesel heater with multi-controller
- Hot air distributed to the saloon, all three cabins and head, with closable outlets

LEE CLOTH KITS FOR AFT CABINS

- · Lee cloth fixation between both berths in the aft cabins
- Two pieces, one for each cabin

BLINDS & MOSQUITO NETS ON PORTHOLES

- · Lewmar roller shades for all hatches on the cabin
- · Combination of blinds and mosquito nets, secured with magnets
- Lewmar roller port shades for both aft cabins portholes

*MLC: Mass of the boat in Light Craft Condition includes the weight of the boat in the standard ready-tonavigate configuration, keel, standard equipment, sails (mainsail & jib) and engine.

Beneteau First 36 - Standard Configuration & Options list, Version 1.2, ENG_INT, March 2022

Seascape d.o.o., Podpeč 53, 1352 Preserje Slovenia. Specifications and descriptions are provided only for your guidance and are subject to change without prior notice.

www.beneteau.com